

VERSION CABINADA SILENT VERSION

MARCA MOTOR: ENGINE BRAND:



MODELO MODEL	480V 3PH Trifásico Three-phase		480V 3PH Trifásico Three-phase		ENGINE MOTOR							TABLERO DE CONTROL CONTROL PANEL	L W H			Kg	dBa @7m
	kW PRP	kVA PRP	kW LTP	kVA LTP		modelo model	refrigera- cion cool.		cilindros cylinders	cm ³				L mm	W mm		
DYNAMIC GU25CS	18	23	20	25	X2.5G4		Diesel	3	2500	70	13	QFIA-4520	1930	800	1230	650	67
STRONG GU40CS	29	36	32	40	X3.3G2		Diesel	4	3300	100	14	QFIA-4520	2213	960	1258	1076	70
STRONG GU50CS	36	45	40	50	S3.8G8		Diesel	4	3800	100	11	QFIA-4520	2213	960	1258	1247	67
KING GU80CS	54	68	60	75	S3.8G10		Diesel	4	3800	150	12	QT2A-4520	2250	1056	1700	1390	67
QUEEN GU100CS	82	102	90	112	6BTA 5.9G6		Diesel	6	5900	270	12	QT2A-4520	2950	1056	1900	1500	67
QUEEN GU130CS	91	114	100	125	6BTA 5.9G6		Diesel	6	5900	270	12	QT2A-4520	2950	1056	1900	1685	70
ROYAL GU150CS	120	150	136	170	6BTAA5.9G6		Diesel	6	5900	350	11	QT2A-4520	3600	1226	2000	1900	70
ROYAL GU200CS	144	180	158	198	QSB7G4		Diesel	6	6690	350	9	QT2A-4520	3600	1226	2000	2100	69
ROYAL GU230CS	160	200	176	220	QSB7G4		Diesel	6	6690	350	9	QT2A-4520	3600	1226	2000	2100	69
ROYAL GU250CS	180	225	200	250	QSB7G5		Diesel	6	6690	350	9	QT2A-4520	3600	1226	2000	2225	69
ROYAL GU300CS	227	284	250	313	QSL9G3		Diesel	6	8800	350	6	QT2A-4520	3600	1226	2000	2255	69
ROYAL GU375CS	275	344	300	375	QSL9G5		Diesel	6	8800	350	6	QT2A-4520	3600	1226	2000	3000	69
MAGNUM GU500CS	364	455	400	500	QSX15G6		Diesel	6	15000	620	8	QT2A-4520	4500	1666	2250	5200	69
MAGNUM GU600CS	450	563	500	625	QSX15G9		Diesel	6	15000	620	7	QT2A-4520	4500	1666	2250	5200	69
EXTREME GU750CS	545	681	600	750	VTA28G5		Diesel	12	28000	400	3	QTVA-7320	5700	2200	3000	9300	69
EXTREME GU1000CS	727	909	800	1.000	QSK23G3		Diesel	6	23100	400	3	QTVA-7320	5666	2200	3126	9520	69
EXTREME GU1100CS	823	1.029	900	1.125	QST30G3		Diesel	12	30500	400	3	QTVA-7320	8600	2200	3000	11500	69
EXTREME GU1300CS	920	1.150	1.012	1.265	QST30G4		Diesel	12	30500	400	2	QTVA-7320	8600	2200	3100	14000	69
EXTREME GU1600CS	1.135	1.419	1.280	1.600	KTA 50G3		Diesel	16	50000	400	2	QTVA-7320	8600	2200	3400	14300	69

LEYENDA:	LEGENDA:
C Motor CUMMINS	CUMMINS engine
S Version cabinada	Silent version
Refrigerado por agua	Water cooled
Autonomía con 75% de la carga	Autonomy at 75% load

También disponibles modelos de potencia mayor.
Available also bigger power models.

Consulte las páginas de 28 a 37 para todos los ratings disponibles con alternador estándar o sobredimensionado.
See pages from 28 to 37 for all available voltages with standard and oversized alternators.

PROFUNDIZACIÓN - COMPLEMENTS	
p. 24 Estructura	Structure
p. 28 Ratings	Ratings
p. 38 Tablero de control	Control panel
p. 42 Cuadros automáticos de transferencia	ATS
p. 44 Controladores	Controllers
p. 46 Detalles de estructura	Structure details
p. 48 Accesorios	Accessories
p. 50 ISO container	ISO container
p. 51 Versiones especiales	Special Versions

